

sgapiGetTableQuestionTitles(%%questionID)

Last Modified on 08/06/2014 1:22 pm EDT

This function accepts the Question ID of a table and returns an array in the following format:
[questionID] => "title"

Example

In this example we output the array of table question titles to the page.

[Check it out in an Example Survey](#)

```
%%output .= sgapiPrint_R(sgapiGetTableQuestionTitles(2));
```

The output would be: Array ([52] => Tetris [53] => Donkey Kong [54] => Super Mario Brothers [55] => Space Invaders [56] => Pong [57] => Solitaire [58] => Minesweeper [59] => Snake [60] => Frogger)

Below is the example from our pipe from a table working example. *To learn more visit our ["Pipe" From a Table Tutorial](#).*

[Check it out in an Example Survey](#)

```
%%original_table = sgapiGetTableQuestionTitles(51);
%%followup_table = sgapiGetTableQuestionTitles(61);
%%row_to_hide = array();
foreach(%%original_table as %%row_id => %%row_title)
{
    if(sgapiGetValue(%%row_id) != 4 && sgapiGetValue(%%row_id) != 5)
    {
        %%row_to_hide[] = %%row_title;
    }
}

foreach(%%followup_table as %%row_id => %%row_title)
{
    sgapiHideQuestion(%%row_id,false);
    foreach(%%row_to_hide as %%title)
    {
        if(%%title == %%row_title)
        {
            sgapiHideQuestion(%%row_id,true);
        }
    }
}
```