This function constructs and sends an email at the runtime of your custom script.

sgapi Email Send (%%to, %%to Name, %%from, %%from Name, %%subject, %%text Body, %%html Body, %%bcc, %%mail Reply To, %%type, %%attachments)

Parameters*

- %%to The recipient's email address.
- %%toName The recipient's name.
- %%from The sender's email address.
- %%fromName The sender's name.
- %%subject The subject line.
- %%textBody The plain text email body.
- %%htmlBody The html formatted email body.
- %%bcc bcc email address (can be an array).
- %%mailReplyTo Send replies to email address.
- %%type The type of email to send "text" or "html."
- %%attachments Email attachments (can be an array).

Example

The below script will send a response confirmation to the respondent. The script is run and the email is sent when the page is displayed. Logic can be set up with in the script or on the logic tab within the application to conditionally run the action and send the email.

^{*}All parameters must be present

```
%%to = sgapiGetValue(7);
%%toName = sgapiGetValue(1);
%%textBody = '';
%%bcc = '';
%%htmlBody = "Thank you for completing the survey. Your response is appreciate
d
We will be in touch shortly!.

Thanks,
Your Company";

sgapiEmailSend(%%to, %%toname, "your.company@company.com", "Your Company", "Your Assessment Results", %%textBody, %%htmlBody, %%bcc, %%to, "html");
```